




RF Wireless LED Digital Clock Series


Improve efficiency and productivity with highly visible synchronized time throughout an entire facility.

TimeTrax Sync™ RF Wireless Synchronized LED Digital Clocks receive a dependable time signal from RF Wireless Transmitter (sold separately). The compact transmitter broadcasts time signal over 128 signaling channels (902-928MHz) to ensure time transmission with no interference. Transmitter requires no FCC license for operation and includes TimeTrax Sync™ software interface for NTP server selection. TimeTrax Sync™ Digital Clocks are available in a variety of bezel colors, LED colors and digit formats (00:00 or 00:00:00) to meet the timekeeping needs of any environment. The TimeTrax Sync™ RF Wireless LED Digital Clock System is simple to install and easy to expand.



Clocks receive time from transmitter

- Receives official, accurate time signal from RF Wireless Transmitter
- Transmitter broadcasts time signal using frequency-hopping 902-928 MHz (128 signaling channels) to ensure no interference
- No FCC license required for operation
- Available in a variety of bezel colors, LED colors and digit formats (00:00 or 00:00:00)
- Ultra bright LED digits provide optimum visibility (up to 250ft)
- Automatic Daylight Saving Time adjustment
- Includes anti-theft wall bracket for safe and secure wall mounting
- Three-year manufacturer's limited warranty



Time Signal "hops" from frequency to frequency, ensuring clocks receive the correct time despite interference on other frequencies.

RF Wireless LED Digital Clock Series Ordering Information

TIMETRAX SYNC™ 4 DIGIT SERIES 00:00	
Part No.	Description
9D34BR	Red LED, 3" Digit, 4-Digit, Black Bezel
9D34SR	Red LED, 3" Digit, 4-Digit, Silver Bezel
9D44BR	Red LED, 4" Digit, 4-Digit, Black Bezel
S9D4R4GALS	Red LED, 4" Digit, 4-Digit, Silver Bezel

TIMETRAX SYNC™ 6 DIGIT SERIES 00:00:00	
Part No.	Description
S9D2B6GALB	Blue LED, 2.5" Digit, 6-Digit, Black Bezel
S9D2B6GALS	Blue LED, 2.5" Digit, 6-Digit, Silver Bezel
9D26BR	Red LED, 2.5" Digit, 6-Digit, Black Bezel
S9D2R6GALS	Red LED, 2.5" Digit, 6-Digit, Silver Bezel
9D46BR	Red LED, 4" Digit, 6-Digit, Black Bezel
S9D4R6GALS	Red LED, 4" Digit, 6-Digit, Silver Bezel

*TimeTrax Sync™ RF Wireless Transmitter required (part #9T1W1 or part #S9DWXSLAUB) for clock operation.







RF Wireless LED Digital Clock Series

SPECIFICATIONS


Time Base	Microprocessor		
Time Update Frequency	Every 20 seconds		
Time Update Method	902-928 MHz RF Wireless Frequency Hopping		
Power	105-240V AC 50/60Hz 12" leads		
Average Current Consumption	<1W		
Operating Temperature	-30° F (-33.44° C) to 130° F (54.44° C)		
Mounting	Double Face, Wall or Ceiling		
Lens Material	Non glare, shatterproof transparent polycarbonate		
Bezel Material	Reinforced Acrylonitrile Butadiene Styrene (ABS)		
Bezel Color	Black or Silver		
Time Format Modes	12 Hour (AM/PM) or 24 Hour (Military)		
LED Color	Red or Blue		
DIGIT HEIGHT/FORMAT	WEIGHT	DIMENSIONS (WXHXD)	SHIPPING WEIGHT
2.5"/6-Digit 00:00:00	1.9lbs (.86kg)	11.25" x 4.5" x 1.5" (28.25cm x 11.5cm x 3.75cm)	1.7lbs (.77kg)
3"/4-Digit 00:00	1.55lbs (.70kg)	11.25" x 4.5" x 1.5" (28.25cm x 11.5cm x 3.75cm)	2.3lbs (1.04kg)
4"/4-Digit 00:00	1.95lbs (.88kg)	11.5" x 6.25" x 1.5" (29cm x 15.75cm x 3.75cm)	2.6lbs (1.17kg)
4"/6-Digit 00:00:00	2.8lbs (1.27kg)	15.5" x 6.25" x 1.5" (39cm x 15.75cm x 3.75cm)	3.05lbs (1.38kg)
Warranty	3-Year manufacturer's limited warranty		
Guarantee	30-Day money back guarantee		
Compliance	FCC part 15 section 15.247 FCC ID# WC7H9ALG1		
Includes	Security wall bracket and key, User Guide		




2.5" x 6 Digit Series



3" x 4 Digit Series



4" x 4 Digit Series




4" x 6 Digit Series

ACCESSORIES

9T1W1*	Ethernet RF Wireless Transmitter, shelf unit (includes software)
S9DWXSLAUB*	Ethernet RF Wireless Transmitter, wall mount unit (includes software)
S9DSXOLAUB	Ethernet RF Wireless Transmitter, shelf unit (add-on transmitter)
42337	Ethernet RF Wireless Transmitter, wall unit (add-on transmitter)
42328	GPS Signal Receiver
42317	RF Wireless Transmitter Wall Rack
42321	Dual Digital Clock Wall Bracket (3x4/2.5x6/4x4)
42443	Dual Analog & Digital Clock Ceiling Bracket
42316	4" x 6-Digit Wire Clock Guard
42400	4" x 4-Digit Wire Clock Guard
42401	2.5" x 6-Digit Wire Clock Guard
42689	18.25" x 9.25" Polycarbonate NEMA4 Clock Cover
42247	Digital Security Mount Replacement
42281	Wall Clock Security Mount Replacement Key

*Either model required for clock operation.



Simple Setup.

Simply plug the RF Wireless transmitter (sold separately) into a standard electrical outlet and Ethernet port to establish a network connection. Transmitter sends time signal to wall clocks.

