

# QUANTUM Q7000iP SERIES

## MULTI-TENANTS BROWSER BASED TELEPHONE ENTRY SYSTEM



250 tenants, 600 cards and 600 codes

Remote programmable, Browser Based

Programming via LAN, WAN, Direct Connect or System's Keypad

No Dedicated IP needed

Backlit Keypad

Brushed stainless steel, dark gray powder coated back box

Surface and Flush Mount / Indoor or Outdoor

24 months warranty

FEATURES	PART#: Q7000iP (Surface Mount)	PART#: Q7000iPFF (Flush Mount)
Input Power	12VAC/12VDC Transformer Included	12VAC/12VDC Transformer Included
Current Consumption	1200mA	1200mA
Operating Temperature	10°F to 145°F	10°F to 145°F
Liquid Crystal Display	16 x 1, Viewing area 99mm x 13mm	16 x 1, Viewing area 99mm x 13mm
Tenant Capacity	250	250
Card Capacity	600, <i>card reader is optional</i>	600, <i>card reader is optional</i>
Code Capacity	600	600
26-Bit Wiegand Input	1, <i>card reader is optional</i>	1, <i>card reader is optional</i>
Auto Door Schedules	10	10
Time Zones	10	10
Holidays	20	20
Temporary cards/codes	10 cards/codes up to 10 times used	10 cards/codes up to 10 times used
Unlock Hold Door with cards/codes	10 cards/codes	10 cards/codes
Unlock Hold Door Timer	1-98 hours	1-98 hours
QWCM ip module	included	included
Telephone line	analog dial tone	analog dial tone
Remote access touch-tone phone	yes, programable	yes, programable
Dry Contact Relay	2	2
Door Sensor	2	2
Postal Lock Ready	yes	yes
Auxiliary Input	2, Programmable	2, Programmable
Analog pin hole color camera	<i>optional</i>	<i>optional</i>
Satellite Access Control RS-485	max. 8 card reader, keypad, or combo	max. 8 card reader, keypad, or combo
Event report	600 buffer	600 buffer
Dimension (HWD)	10-13/16" x 8-5/8" x 3-3/4"	14-5/16" x 12-1/8" x 2-5/8" (Total Dimension) 11-1/8" x 8-11/16" x 2-5/8" (Inside Ring)

### ACCESSORIES

**QVPC:** Analog color camera  
**USP1:** AC and Telephone surge protector  
**USP2L:** Surge and Lightning protection  
**UBAT1:** 12VDC 4.5 Ahr backup battery  
**IREXIT:** Infrared exit switch  
**AHP5:** Heater-pad

**USCR:** Satellite card reader  
**USKP:** Satellite keypad  
**USKPR:** Satellite reader/keypad combo  
**UCRM:** Satellite RS-485 controller  
**UWCR:** 26-Bit card reader  
**UFOB:** Keyfob

**UCLAM:** Clam shell card  
**UIISO:** ISO card  
**UPM1S:** 42" H Single arm pedestal  
**UPM2:** Dual vertical arm pedestal  
**UPM5:** Dual horizontal arm pedestal  
**UPM6L:** 64" H Single arm pedestal