

QUANTUM Q7000VOIP SERIES

MULTI-TENANTS BROWSER BASED VOIP TELEPHONE ENTRY SYSTEM



24 months warranty

250 tenants, 600 cards and 600 codes

Nominal monthly fees and taxes required based on zip code for activation

Remote programmable, Browser Based

Programming via LAN, WAN, Direct Connect or System's Keypad.

No Dedicated IP needed

Backlit Keypad

Brushed stainless steel, dark gray powder coated back box

Surface and Flush Mount / Indoor or Outdoor, QATA2 Indoor only

FEATURES	Q7000VOIP (Surface Mount)	Q7000VOIPFF (Flush Mount)
Input Power	12VAC/12VDC Transformer Included	12VAC/12VDC Transformer Included
Current Consumption	1200mA	1200mA
Operating Temperature	10°F to 145°F	10°F to 145°F
Liquid Crystal Display	16 x 1, Viewing area 99mm x 13mm	16 x 1, Viewing area 99mm x 13mm
Tenant Capacity	250	250
Card Capacity	600, <i>card reader is optional</i>	600, <i>card reader is optional</i>
Code Capacity	600	600
26-Bit Wiegand Input	1, <i>card reader is optional</i>	1, <i>card reader is optional</i>
Auto Door Schedules	10	10
Time Zones	10	10
Holidays	20	20
Temporary cards/codes	10 cards/codes up to 10 times used	10 cards/codes up to 10 times used
Unlock Hold Door with cards/codes	10 cards/codes	10 cards/codes
Unlock Hold Door Timer	1-98 hours	1-98 hours
QWCM ip module	included	included
AATA2 VOIP (included)	Nominal monthly fees and taxes required based on zip code for activation	Nominal monthly fees and taxes required based on zip code for activation
Remote access touch-tone phone	yes, programable	yes, programable
Dry Contact Relay	2	2
Door Sensor	2	2
Postal Lock Ready	yes	yes
Auxiliary Input	2, Programmable	2, Programmable
Analog pin hole color camera	<i>optional</i>	<i>optional</i>
Satellite Access Control RS-485	max. 8 card reader, keypad, or combo	max. 8 card reader, keypad, or combo
Event report	600 buffer	600 buffer
Dimension (HWD)	10-13/16" x 8-5/8" x 3-3/4"	14-5/16" x 12-1/8" x 2-5/8" (Total Dimension) 11-1/8" x 8-11/16" x 2-5/8" (Inside Ring)

ACCESSORIES

QVPC: Analog color camera

USP1: AC and Telephone surge protector

USP2L: Surge and Lightning protection

UBAT1: 12VDC 4.5 Ahr backup battery

IREXIT: Infrared exit switch

AHP5: Heater-pad

USCR: Satellite card reader

USKP: Satellite keypad

USKPR: Satellite reader/keypad combo

UCRM: Satellite RS-485 controller

UWCR: 26-Bit card reader

UFOB: Keyfob

UCLAM: Clam shell card

UIISO: ISO card

UPM1S: 42" H Single arm pedestal

UPM2: Dual vertical arm pedestal

UPM5: Dual horizontal arm pedestal

UPM6L: 64" H Single arm pedestal