

QUANTUM QC SERIES

MULTI-TENANTS BROWSER BASED TELEPHONE ENTRY SYSTEM

100-600 tenants, 300-3000 cards and 300-1000 codes



Remote programmable, Browser Based

Programming via LAN, WAN, Direct Connect or System's Keypad

No Dedicated IP needed

Backlit Keypad

Brushed stainless steel, dark gray powder coated back box

Surface and Flush Mount / Indoor or Outdoor

24 months warranty

| FEATURES | QC1 Surface Mount | QC1FF Flush Mount | QC1iP Surface Mount | QC1iPFF Flush Mount | QC2iP Surface Mount | QC2iPFF Flush Mount | QC6iP Surface Mount | QC6iPFF Flush Mount |
|------------------------|--|----------------------|------------------------|------------------------|---|------------------------|------------------------|------------------------|
| Input power included | 12Vac/12Vdc | 12Vac/12Vdc | 12Vac/12Vdc | 12Vac/12Vdc | 12Vac/12Vdc | 12Vac/12Vdc | 12Vac/12Vdc | 12Vac/12Vdc |
| Current consumption | 900mA | 900mA | 1150mA | 1150mA | 1150mA | 1150mA | 1150mA | 1150mA |
| Operating temperature | 10-145 °F | 10-145 °F | 10-145 °F | 10-145 °F | 10-145 °F | 10-145 °F | 10-145 °F | 10-145 °F |
| Liquid Crystal Display | 16 x 1 | 16 x 1 | 16 x 1 | 16 x 1 | 16 x 1 | 16 x 1 | 16 x 1 | 16 x 1 |
| Tenant capacity | 100 | 100 | 100 | 100 | 250 | 250 | 600 | 600 |
| Code capacity | 300 | 300 | 300 | 300 | 1000 | 1000 | 600 | 600 |
| Card capacity | 300 | 300 | 300 | 300 | 1000 | 1000 | 3000 | 3000 |
| 26-Bit Wiegand Input | 1, incl.reader | 1, incl.reader | 1, incl.reader | 1, incl.reader | 1, incl.reader | 1, incl.reader | 1, incl.reader | 1, incl.reader |
| Auto Door Schedules | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 |
| Time Zones | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 |
| Holidays | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 |
| Temp. cards/codes | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 |
| Unlock holdcards/codes | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 |
| Unlock hold timer | 1-98 hours | 1-98 hours | 1-98 hours | 1-98 hours | 1-98 hours | 1-98 hours | 1-98 hours | 1-98 hours |
| QWCM iP module | optional | optional | included | included | included | included | included | included |
| Telephone line | analog | analog | analog | analog | analog | analog | analog | analog |
| Remote access | yes | yes | yes | yes | yes | yes | yes | yes |
| Dry contact relay | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| Door sensor | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| Auxiliary input | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| Event recording buffer | 600 | 600 | 600 | 600 | 600 | 600 | 600 | 600 |
| Slave access control | max. 8 | max. 8 | max. 8 | max. 8 | max. 8 | max. 8 | max. 8 | max. 8 |
| Dimension (HWD) | 6-7/16" x 10-3/8" x 3-1/2" (SURFACE MOUNT) | | | | 9-13/16" x 11-13/16" x 3-5/8" (Flush mount) (TOTAL DIMENSION) 7-1/2" x 10-1/2" x 3-5/8" (inside Ring) | | | |

ACCESSORIES

QVPC: Analog color camera

USP1: AC and Telephone surge protector

USP2L: Surge and Lightning protection

UBAT1: 12VDC 4.5 Ahr backup battery

IREXIT: Infrared exit switch

AHP5: Heater-pad

USCR: Satellite card reader

USKP: Satellite keypad

USKPR: Satellite reader/keypad combo

UCRM: Satellite RS-485 controller

UWCR: 26-Bit card reader

UFOB: Keyfob

UCLAM: Clam shell card

UIISO: ISO card

UPM1S: 42" H Single arm pedestal

UPM2: Dual vertical arm pedestal

UPM5: Dual horizontal arm pedestal

UPM6L: 64" H Single arm pedestal



PACH AND COMPANY INC.
CALIFORNIA ■ 949-498-2951 ■ 1-888-678-7224