

Reolink-Duo-Floodlight-PoE-IP-Camera-Specifications			
	Model	Reolink Duo Floodlight PoE	
Video & Audio	Image Sensor	1/2.7" CMOS Sensors	
	Video Resolution	Default: 4608X1728 (8.0 megapixels) at 20 frames/sec	
	Lens	f = 3.2 mm fixed, F = 2.0	
	Video Format	H.265	
	Field of View	Horizontal:	180°
		Vertical:	60°
	Day & Night	Auto-switching with IR cut filter	
	Infrared Night Vision	30 meters (LED: 14pcs/20mil/850nm)	
	Color Night Vision	Floodlight: 40pcs SMD LEDs/15W/4200K/1800 Lumens	
Audio	Two-way audio		
Power	POE	IEEE 802.3at, 48V Active	
	DC Power	DC 12V=1.7A, <24W	
Interface	Power	DC power port	
	System	Reset button	
	Ethernet	One 10M/100Mbps; RJ45	
	Storage	Micro SD card slot (Max. 256GB)	
	Audio	Built-in microphone and speaker	
Software Features	Frame Rate	Mainstream: 4fps - 20fps (default: 20fps)	
		Substream: 4fps - 20fps (default: 10fps)	
	Code Rate	Mainstream: 3072-10240Kbps (default: 8192kbps)	
		Substream: 256-2048Kbps (default: 1024kbps)	
	Browser Supported	Edge, Chrome, Firefox, Safari	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Smart Alarm	Motion detection; person detection; vehicle detection; pet detection	
	Record Mode	Motion-triggered recording (default); scheduled recording	
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P	
Maximal User Access	20 Users (1 admin account & 19 user accounts); Supports up to 12 simultaneous video streams (10 substreams & 2		
Works with	Google Assistant		
Working Environment	Temperature	Operating temperature: -10°C~+50°C (14°F~122°F)	
	Humidity	Operating humidity: 10% ~ 90%	
	Waterproof	IP66	
Size & Weight	Dimension	243x210x151 mm	
	Weight	1.25kg	
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/	