

Reolink-Go-PT-Plus-IP-Camera-Specifications		
	Model	Reolink Go PT Plus
Video & Audio	Image Sensor	1/3" CMOS Sensor
	Video Resolution	2560 x 1440 (4.0 megapixel) at 15 frames/sec
	Video Format	H.265
	Field of View	Fixed lens, horizontal: 95°, vertical: 57°, 115° diagonal
	Infrared Night Vision	Up to 10 meters (33ft) (LED: 6pcs/14mil/850nm)
	Digital Zoom	10X digital zoom
	Audio	Two-way audio
PIR Detection & Alerts	Smart Alarm	PIR detection/human detection/vehicle detection
	PIR Detecting Distance	Adjustable up to 10m (33ft)
	PIR Detecting Angle	120° horizontal
	Audio Alert	Customizable verbal alerts
	Recording	Motion-triggered recording
	Other Alerts	Instant email alerts and push notifications
3G/4G	 Frequency Bands	Europe LTE FDD: B1/B3/B7/B8/B20 WCDMA: B1/B8
		America LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5
		Australia LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8
	Transmission Data	LTE FDD: Max. 10Mbps (DL), Max. 5Mbps (UL)
LTE TDD: Max. 8.96Mbps (DL), Max. 3.1Mbps (UL)		
HSPA+: Max. 42Mbps (DL), Max. 5.76Mbps (UL)		
UMTS: Max. 384Kbps (DL), Max. 384Kbps (UL)		
Power	Battery	6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature.)
	Solar	Reolink Solar Panel (optional)
	DC Power	5V/2A USB power adapter
Storage	Local Storage	Micro SD card slot (supports Max. 128GB; includes a 32GB micro SD card)
	Cloud Storage	Supports Reolink Cloud (available in some countries)
Smart Home	Smart Home	Works with Google Assistant
Working Environment	Operating Temperature	-10°C to 55°C (14°F to 131°F)
	Weather Resistance	IP64 Weatherproof
Size & Weight	Size	Φ98 x 112mm (Φ3.7 x 4.4 in)
	Weight (Battery Included)	485g (17.1 oz)
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .