

RLK8-1200B4-A-4.0mm-IP-Camera-B1200-Specification			
	Model	B1200 (4.0mm)	
Note:	The cameras of the kit cannot work without the NVR.		
Video & Audio	Image Sensor	1/2.49" CMOS Sensor	
	Video Resolution	Default: 4512X2512 (12 megapixels) at 20 fps	
	Lens	f=4.0mm; F=1.6, with IR-cut filter	
	Video Format	H.265	
	Field of View	Horizontal:	93°
		Vertical:	49°
	Day & Night	Auto-switching with IR-cut filter	
	Infrared Night Vision	30 meters (LED: 2pcs/28mil/850nm)	
	Color Night Vision	Spotlight: 1pcs/4.3W/6500K/700 Lumens	
Audio	Two-way audio (via Reolink App/Client)		
Power	POE	IEEE 802.3af, 48V Active	
	DC Power	DC 12.0V= 1A, <12W	
Interface	Power	DC power port	
	System	Reset button	
	Ethernet	One 10M/100Mbps; RJ45	
	Audio	Built-in microphone and speaker	
Software Features	Frame Rate	Mainstream: 2fps - 20fps (default: 20fps)	
		Substream: 4fps - 20fps (default: 10fps)	
	Code Rate	Mainstream: 3072Kbps - 10240Kbps (default: 8192Kbps)	
		Substream: 128Kbps - 1024Kbps (default: 768Kbps)	
Smart Alarm	Motion detection; person detection; vehicle detection; pet detection		
Working Environment	Temperature	Operating temperature: -10° C~+55° C (14° F~131° F)	
	Humidity	Operating humidity: 10% ~ 90%	
	Waterproof	IP66	
Size & Weight	Dimension	Φ67*187mm	
	Weight	460g	
Warranty	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>	