

TrackMix-PoE-IP-Camera-Specifications			
	Model	Reolink TrackMix PoE	
Video & Audio	Image Sensor	1/3"+1/2.8"CMOS Sensor	
	Video Resolution	Up to: 3840 x 2160 (8.0 megapixels) at 25 frames/sec	
	Lens	f=2.8mm@F=1.6, f=8mm@F=1.6	
	Video Format	H.264, H.265	
	Field of View	Horizontal:	104°-38°
		Vertical:	60°-21°
	Zoom Mode	6X hybrid zoom	
	Day & Night	IR-cut filter with auto-switching	
	Infrared Night Vision	Up to 30 meters (100ft) (LED: 2pcs/850nm)	
	Color Night Vision	Spotlights: 2pcs/6500K/450 lumens	
Power	Audio	Two-way audio	
	PoE	IEEE 802.3af, 48V active	
Interface	DC Power	DC 12.0V=2A, <12W	
	Power	DC power port	
	System	Reset button	
	Ethernet	One 10M/100Mbps RJ45	
	Storage	Micro SD card slot (Max. 256GB)	
Pan&Tilt	Audio	Built-in microphone and speaker	
	Pan &Tilt Range	Pan: 355°, Tilt: 0°~90°	
	Pan Speed	2.5°-90°/s (Speed can be set)	
	Tilt Speed	1.5°-60°/s (Speed can be set)	
	Preset	32	
Software Features	Auto Tracking	Support	
	Frame Rate	Mainstream:	2fps - 25fps
		Substream:	4fps - 20fps
	Code Rate	Mainstream:	4096Kbps -8192Kbps
		Substream:	128Kbps -1228Kbps
	Browsers Supported	Edge, Chrome, Firefox, Safari	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Smart Alarms	Motion detection; person detection; vehicle detection; pet detection	
	Recording Modes	Motion/scheduled recording (default: motion recording)	
	Tracking Method	Digital Tracking; Pan/Tilt Tracking First; Digital Tracking First	
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P		
Maximal User Access	Supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams) 20 users (1 admin account & 19 user accounts);		
Working Environment	Work with	Google Assistant	
	Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)	
	Humidity	Operating humidity: 10% ~ 90%	
Size & Weight	Waterproof	IP65	
	Dimension	228*147*110mm	
Warranty	Weight	1.21KG	
	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> .	