

Reolink-Video-Doorbell-PoE-Black-Specifications

	Model	Reolink Video Doorbell PoE (Black)	
Video & Audio	Image Sensor	1/2.7" CMOS Sensor	
	Video Resolution	Default: 2560×1920 (5 megapixels) @20FPS	
	Lens	f=2.26mm F=2.0, with IR cut	
	Video Format	H.264	
	Field of View		Horizontal: 135°
			Vertical: 100°
			Diagonal: 180°
	Pre-Motion Recording	YES	
Audio	Two-way audio, noise reduction, echo suppression		
Quick Replies	YES		
Power	PoE	IEEE 802.3af, 48V Active	
	Hardwired	12 – 24VAC 50/60Hz, 24VDC	
Interface	Power	Power port	
	System	Reset button	
	Ethernet	One 10M/100Mbps RJ45	
	Storage	microSD card slot (Max. 256GB), works with Reolink NVR	
	Audio	Built-in two microphones & one speaker	
Software	Frame Rate	Mainstream: 2fps - 20fps (default: 20fps)	
		Substream: 4fps - 15fps (default: 10fps)	
	Code Rate	Mainstream: 1024Kbps - 6144Kbps (default: 4096Kbps)	
		Substream: 64Kbps - 512Kbps (default: 256Kbps)	
	Browsers Supported	Edge, Chrome, Firefox, Safari	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Smart Alarm	Motion detection/person detection; visitor notification	
	Recording Modes	Motion recording (default); 24/7 recording; scheduled recording	
Protocols & Standards	HTTPS, IPv4, UPNP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P		
Working Environment	Work with	Google Assistant	
	Temperature	Operating temperature: -10°C – +55°C (14°F–131°F)	
	Humidity	Operating humidity: 10%–90%	
	Weatherproof	IP65	
Size & Weight	Dimension	133mm (H) ×48mm (W) ×23mm (T)	
	Weight	96g	
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .	

Reolink-Video-Doo	
	Model
Video & Audio	Image Sensor
	Video Resolution
	Lens
	Video Format
	Field of View
	Pre-Motion Recording
	Audio
	Quick Replies
Power	PoE
	Hardwired
Interfaces	Power
	System
	Ethernet
	Storage
	Audio
Software	Frame Rate
	Code Rate
	Browsers Supported
	OS Supported
	Smart Alarm
	Recording Modes
	Protocols & Standards
	Work with
Working Environment	Temperature
	Humidity
	Weatherproof
Size & Weight	Dimension
	Weight
Warranty	Limited Warranty

Reolink Video Doorbell PoE (White)
1/2.7" CMOS Sensor
Default: 1920×2560 (5 megapixels) @20FPS
f=2.26mm F=2.0, with IR cut
H.264
Horizontal: 100°
Vertical: 135°
Diagonal: 180°
YES
Two-way audio, noise reduction, echo suppression
YES
IEEE 802.3af, 48V Active
12 – 24VAC 50/60Hz, 24VDC
Power port
Reset button
One 10M/100Mbps RJ45
microSD card slot (Max. 256GB), works with Reolink NVR
Built-in two microphones & one speaker
Mainstream: 2fps - 20fps (default: 20fps)
Substream: 4fps - 15fps (default: 10fps)
Mainstream: 1024Kbps - 6144Kbps (default: 4096Kbps)
Substream: 64Kbps - 512Kbps (default: 256Kbps)
Edge, Chrome, Firefox, Safari
PC: Windows, Mac OS; Smartphone: iOS, Android
Motion detection/person detection; visitor notification
Motion recording (default); 24/7 recording; scheduled recording
HTTPS, IPv4, UPNP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Google Assistant
Operating temperature: -10°C – +55°C (14°F–131°F)
Operating humidity: 10% – 90%
IP65
133mm (H) ×48mm (W) ×23mm (T)
96g
2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Reolink-Chime-US-Version-Specifications		
	Model	Reolink Chime (US Version)
Physical	Material	ABS+PC
	Dimensions	86.5 x 29 x 45.2 mm
General	Input	AC 100-240 V; 50-60 Hz
	Button	For setting up/selecting ringtones/adjusting volume
	Transmission Mode	RF 433 MHz
	Volume	5 levels
	Number of Selectable Ringtones	10 ringtones
	Working Environment	Temperature: -20°C~50°C; Humidity: <85%
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Reolink-Chime-EU-Version-Specifications		
	Model	Reolink Chime (EU Version)
Physical	Material	ABS+PC
	Dimensions	86.5 x 29 x 66 mm
General	Input	AC 100-240 V; 50-60 Hz
	Button	For setting up/selecting ringtones/adjusting volume
	Transmission Mode	RF 433 MHz
	Volume	5 levels
	Number of Selectable Ringtones	10 ringtones
	Working Environment	Temperature: -20°C~50°C; Humidity: <85%
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Reolink-Chime-UK-Version-Specifications		
	Model	Reolink Chime (UK Version)
Physical	Material	ABS+PC
	Dimensions	86.5 x 29 x 52 mm
General	Input	AC 100-240 V; 50-60 Hz
	Button	For setting up/selecting ringtones/adjusting volume
	Transmission Mode	RF 433 MHz
	Volume	5 levels
	Number of Selectable Ringtones	10 ringtones
	Working Environment	Temperature: -20°C~50°C; Humidity: <85%
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Reolink-Chime-AU-Version-Specifications		
	Model	Reolink Chime (AU Version)
Physical	Material	ABS+PC
	Dimensions	86.5 x 30.6 x 47.6 mm
General	Input	AC 100-240 V; 50-60 Hz
	Button	For setting up/selecting ringtones/adjusting volume
	Transmission Mode	RF 433 MHz
	Volume	5 levels
	Number of Selectable Ringtones	10 ringtones
	Working Environment	Temperature: -20°C~50°C; Humidity: <85%
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .