

Reolink-Video-Doorbell-WiFi-Black-Specifications			
	Model	Reolink Video Doorbell WiFi (Black)	
Video & Audio	Image Sensor	1/2.7" CMOS Sensor	
	Video Resolution	Default: 2560×1920 (5 megapixels) @20FPS	
	Lens	f=2.26mm F=2.0, with IR cut	
	Video Format	H.264	
	Field of View		Horizontal: 135°
			Vertical: 100°
			Diagonal: 180°
	Pre-Motion Recording	YES	
Audio	Two-way audio, noise reduction, echo suppression		
Quick Replies	YES		
Power	Hardwired	12 24VAC 50/60Hz, DC 24V	
Interface	Power	Power port	
	System	Reset button	
	Ethernet	One 10M/100Mbps RJ45	
	Storage	microSD card slot (Max. 256GB), works with Reolink NVR	
	Audio	Built-in two microphones & one speaker	
WiFi	Wireless Standard	IEEE 802.11a/b/g/n	
	Operating Frequency	2.4GHz/5GHz	
	Wireless Security	WPA-PSK/WPA2-PSK	
Software	Frame Rate	Mainstream: 2fps - 20fps (default: 20fps)	
		Substream: 4fps - 15fps (default: 10fps)	
	Code Rate	Mainstream: 1024Kbps - 6144Kbps (default: 4096Kbps)	
		Substream: 64Kbps - 512Kbps (default: 256Kbps)	
	Browsers Supported	Edge, Chrome, Firefox, Safari	
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android	
	Smart Alarm	Motion detection/person detection; visitor notification	
	Recording Modes	Motion recording (default); 24/7 recording; scheduled recording	
Protocols & Standards	HTTPS, IPv4, UPNP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P		
Work with	Google Assistant		
Rich Notification	YES		
Working Environment	Temperature	Operating temperature: -10°C – +50°C (14°F – 122°F)	
	Humidity	Operating humidity: 10% – 90%	
	Weatherproof	IP65	
Size & Weight	Dimension	133mm (H) ×48mm (W) ×23mm (T)	
	Weight	96g	
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .	

Reolin	
	Model
Video & Audio	Image Sensor
	Video Resolution
	Lens
	Video Format
	Field of View
	Pre-Motion Recording
	Audio
	Quick Replies
Power	Hardwired
Interface	Power
	System
	Ethernet
	Storage
	Audio
WiFi	Wireless Standard
	Operating Frequency
	Wireless Security
Software	Frame Rate
	Code Rate
	Browsers Supported
	OS Supported
	Smart Alarm
	Recording Modes
	Protocols & Standards
	Work with
	Rich Notification
Working Environment	Temperature
	Humidity
	Weatherproof
Size & Weight	Dimension
	Weight
Warranty	Limited Warranty

k-Video-Doorbell-WiFi-White-Specifications
Reolink Video Doorbell WiFi (White)
1/2.7" CMOS Sensor
Default: 1920×2560 (5 megapixels) @20FPS
f=2.26mm F=2.0, with IR cut
H.264
Horizontal: 100°
Vertical: 135°
Diagonal: 180°
YES
Two-way audio, noise reduction, echo suppression
YES
12 24VAC 50/60Hz, DC 24V
Power port
Reset button
One 10M/100Mbps RJ45
microSD card slot (Max. 256GB), works with Reolink NVR
Built-in two microphones & one speaker
IEEE 802.11a/b/g/n
2.4GHz/5GHz
WPA-PSK/WPA2-PSK
Mainstream: 2fps - 20fps (default: 20fps)
Substream: 4fps - 15fps (default: 10fps)
Mainstream: 1024Kbps - 6144Kbps (default: 4096Kbps)
Substream: 64Kbps - 512Kbps (default: 256Kbps)
Edge, Chrome, Firefox, Safari
PC: Windows, Mac OS; Smartphone: iOS, Android
Motion detection/person detection; visitor notification
Motion recording (default); 24/7 recording; scheduled recording
HTTPS, IPv4, UPNP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Google Assistant
YES
Operating temperature: -10°C – +50°C (14°F – 122°F)
Operating humidity: 10% – 90%
IP65
133mm (H) ×48mm (W) ×23mm (T)
96g
2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Reolink-Chime-US-Version-Specifications		
	Model	Reolink Chime (US Version)
Physical	Material	ABS+PC
	Dimensions	86.5 x 29 x 45.2 mm
General	Input	AC 100-240 V; 50-60 Hz
	Button	For setting up/selecting ringtones/adjusting volume
	Transmission Mode	RF 433 MHz
	Volume	5 levels
	Number of Selectable Ringtones	10 ringtones
	Working Environment	Temperature: -20°C~50°C; Humidity: <85%
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Reolink-Chime-EU-Version-Specifications		
	Model	Reolink Chime (EU Version)
Physical	Material	ABS+PC
	Dimensions	86.5 x 29 x 66 mm
General	Input	AC 100-240 V; 50-60 Hz
	Button	For setting up/selecting ringtones/adjusting volume
	Transmission Mode	RF 433 MHz
	Volume	5 levels
	Number of Selectable Ringtones	10 ringtones
	Working Environment	Temperature: -20°C~50°C; Humidity: <85%
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Reolink-Chime-UK-Version-Specifications		
	Model	Reolink Chime (UK Version)
Physical	Material	ABS+PC
	Dimensions	86.5 x 29 x 52 mm
General	Input	AC 100-240 V; 50-60 Hz
	Button	For setting up/selecting ringtones/adjusting volume
	Transmission Mode	RF 433 MHz
	Volume	5 levels
	Number of Selectable Ringtones	10 ringtones
	Working Environment	Temperature: -20°C~50°C; Humidity: <85%
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Reolink-Chime-AU-Version-Specifications		
	Model	Reolink Chime (AU Version)
Physical	Material	ABS+PC
	Dimensions	86.5 x 30.6 x 47.6 mm
General	Input	AC 100-240 V; 50-60 Hz
	Button	For setting up/selecting ringtones/adjusting volume
	Transmission Mode	RF 433 MHz
	Volume	5 levels
	Number of Selectable Ringtones	10 ringtones
	Working Environment	Temperature: -20°C~50°C; Humidity: <85%
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .