





5 MEGAPIXEL 4-IN-1 HD-TVI/AHD/CVI/CVBS FIXED BULLET SECURITY CAMERA WITH 82 FEET NIGHT VISION

Key Specifications:

- + 5MP high definition
- + Video Output: AHD/ TVI: 8M@15fps/12.5fps, 4M@30fps/15fps, 2M@30fps; CVI: 8M@15fps
- + 1/ 2.5" CMOS Sensor
- + .03 Lux Rating
- + Starlight Chipset
- + 3.6mm lens
- + 82 feet Smart IR Distance
- + Audio over Coax
- + DWDR (Digital Wide Dynamic Range)
- + DNR (Digital Noise Reduction)
- + IP67 rating- withstands temps from 14 degrees to 140 degrees Fahrenheit
- + Meets NDAA compliance

5MP 4-in-1 Fixed Bullet Security Camera delivers crisp video day or night, providing HD-TVI/AHD/CVI/CVBS output for compatibility. Connect to other DVRs and Hybrid recorders with one easy solution.

This product has been specifically designed and manufactured to comply with the latest technical requirements specified under NDAA regulations.

Protecting your home or business has never been easier – or more convenient. The 5MP HD-TVI bullet security camera offers an impressive 82 feet IR – perfect for after-hours surveillance or anywhere you need to capture bright footage in dark conditions to protect your business. Whether it's 12pm or 12am, this versatile indoor/outdoor camera provides clear, crisp surveillance

- + Multi-Megapixel Resolution Video 5MP resolution allows you to capture a high level of clarity and detail for most applications
- 3D Digital Noise Reduction (DNR) effectively filters noise to produce a more crisp, clear video stream.
- + **IP67 weatherproof housing** -this camera can handle long-term durability even among extreme weather conditions such as rain, snow, and ice.
- + IllumiNite Technology featuring Starlight chipsets features an HD progressive scan CMOS sensor, capturing clear and vivid color images day or night even in extremely dark environments.

SPECIFICATIONS

CAMERA

| Image Sensor | 1/2.5" CMOS sensor |
|----------------------|--|
| Image Resolution | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | Auto |
| Minimun Illumination | Color: 0.03 lux@F2.0, 0 Lux with white light |
| Scanning System | Progressive Scan |

LENS

| Focus Length | 3.6mm |
|---------------|-------|
| Focus Control | Fixed |
| Lens Type | Fixed |

NIGHT VISION

| IR Cut Filter | YES |
|---------------|-------------------------------|
| Infrared LED | NO, Suport Warm white (4000K) |
| Light Distanc | up to 25m |
| IR Status | AGC auto control |

CAMERA FEATURES

| Starlight | N/A |
|-----------------|-----------------|
| Day/Night | Color |
| OSD Menu | YES |
| WDR | DWDR |
| UTC | YES |
| Noise Reduction | DNR |
| Coaxial Audio | YES (only TVI) |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |

GENERAL

| Housing | Metal, IP67 |
|-----------------------|--------------------------|
| Bracket | YES |
| Operation Temperature | -10°C ~ +60°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 450mA |
| Dimension | 171(W) x 73(H) x 73(D)mm |
| Weight | 750g |

DIMENSIONS

