



128 CHANNEL 4-PORT HDMI DECODING CARD FOR VIDEO WALL

Key Specifications:

- + Support 4-ch HDMI
- + Up to 16 Megapixels resolution
- + HDMI output up to 4K(3840x2160) resolution o All HDMI independent outputs
- + Multi-window 1/4/5/6/7/8/9/16
- + Support H.265/H.264 video formats
- + Only for use with ALI-NR1281X-16

Power up your enterprise network recorder with the 4-Channel HDMI Output Decoding Card. It supports up to 16.0 megapixel input resolution and adds four additional HDMI outputs up to 4k(3840x2160) resolution for ultra-sharp, high-resolution surveillance.

SPECIFICATIONS

MODEL	FB-HD04-B	FB-HD07-B
HDMI Output	HDMI1 & HDMI2: 4K (3840x2160) /60Hz, 4K (3840x2160) /30Hz, 1920x1080 /60Hz, 1920x1080 /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz HDMI3 & HDMI4: 1920x1080 /60Hz, 1920x1080 /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz	HDMI1 & HDMI2 & HDMI3 & HDMI4: 4K (3840x2160) /60Hz, 4K (3840x2160) /30Hz, 1920x1080 /60Hz, 1920x1080 /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz HDMI5 & HDMI6 & HDMI7: 1920x1080 /60Hz, 1920x1080 /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz
Capability	HDMI1 & HDMI2 & HDMI3 & HDMI4: 4 x 16MP@30, 5 x 12MP@30, 8 x 4K@30, 12 x 5MP@30, 16 x 4MP@30, 20 x 3MP@30, 32 x 1080P@30, 54 x 960P@30, 72 x 720P@30, 128 x D1	HDMI1 & HDMI3 & HDMI5 & HDMI7: 4 x 16MP@30, 5 x 12MP@30, 8 x 4K@30, 12 x 5MP@30, 16 x 4MP@30, 20 x 3MP@30, 32 x 1080P@30, 54 x 960P@30, 72x 720P@30, 128 x D1 HDMI2 & HDMI4 & HDMI6: 4 x 16MP@30, 5 x 12MP@30, 8 x 4K@30, 12 x 5MP@30, 16 x 4MP@30, 20 x 3MP@30, 32 x 1080P@30, 54 x 960P@30, 72x 720P@30, 128 x D1
Multi-window	1/4/5/6/7/8/9/16	
Working Temperature	-10°C - + 55°C (14°F to +131°F)	
Working Humidity	10% - 90% (non-condensing)	
Weight	<1 Kg (2.2 lb)	

DIMENSIONS

