

CATALOG NO	VOLTS(V)	__mH ±10%	__AMPS(A)	APPROX WT-LBS	TORQUE(LB-IN)
KLR18BTB	7.20	.620	18	10	20
KLR18FTB	8.62	.734	18	10	20
KLR21BTB	7.20	.525	21	10	20
KLR21FTB	8.62	.629	21	10	20
KLR25BTB	7.20	.441	25	10	20
KLR25FTB	8.62	.528	25	10	20
KLR27BTB	7.20	.408	27	10	20
KLR27FTB	8.62	.489	27	10	20
KLR35BTB	7.20	.315	35	11	20
KLR35FTB	8.62	.377	35	11	20
KLR45BTB	7.20	.245	45	11	20
KLR45FTB	8.62	.294	45	11	20


TC Performance and Protection for Drives.

TRANS-COIL, INC
MILWAUKEE WI
WWW.TRANSCOIL.COM
800-824-8282

KLR Series Line Reactor
CATALOG

3PH, 60Hz, 600V Max, $\frac{1}{2}$ Amps
40C Amb Max, 115C Rise

UL US SR CE



NOTE: A1, A2, B1, B2, C1, C2,
MARKINGS ON TERMINAL BLOCK.
FOR REFERENCE ONLY.

Block Wire Range: #18 to #4 AWG Solid or Stranded, Copper
Tightening Torque: 20 LB-IN

				TOLERANCES EXCEPT AS NOTED
				DECIMAL
				.XX ± .03
				.XXX ± .01
				FRACTIONAL
				± 1/32
				ANGULAR
				± 1/2°
NO	2235, MOUNTING CHG	06/06/03	DSW	
	REVISION	DATE	BY	