

USCR

26-BIT WIEGAND SLAVE CARD READER



- 26-Bit Satellite Reader for all Quantum models
- Up to 8-32 USCR can be interfaced with the models above, contact us for more detail
- Single relay
- Audible tone and LED indicator for valid and invalid access
- Independent access
- Brushed stainless steel, dark gray powder coated back box
- Tamper Proof Screws
- Indoor or outdoor

24 months warranty

TECHNICAL SPECIFICATION

POWER INPUT: 12VAC 40VA or 12VDC 2 Amps (12VAC is supplied by Pach & Company).

CURRENT CONSUMPTION: 50mA Idle, 475mA operation.

EMERGENCY BATTERY: 12VDC, 4Ahr rechargeable (customer supplied).

COMMUNICATION: RS-485 (maximum distance not to exceed 4000 ft, daisy chain connection).

OPERATING ENVIRONMENT: 10°F to 145°F. Relative Humidity 0% to 95%.

RELAY OUTPUT: From C Dry Contact 120VAC 10A/ 24VDC 10 A/ 250VAC 7A with 5 seconds output duration.

MOUNTING: Surface, Indoor or outdoor

CONSTRUCTION: 16 Gauge Cold Rolled Steel with Brushed Stainless Steel Faceplate.

DIMENSION: 6-1/8" (H) x 7-1/16" (W), 1-1/2" (D)

SHIPPING WEIGHT: 5 lbs.

ORDERING PART NUMBER

USCR

OPTIONS AND ACCESSORIES

UIISO: ISO 26 bit wiegand card (credit Card Size)

UFOB: 26 bit wiegand keyfob

UCLAM: 26 bit wiegand card with punch hole for badge holder

USP1: AC and Telephone surge protector

UPM1S: 42" H Single arm pedestal

UPM6L: 64" H Single arm pedestal

UPM2: Double Vertical Arm pedestal

UPM5: Double Horizontal Arm pedestal

UPM12E: 12" Expansion Arm use for all UPMs

 **PACH AND COMPANY INC.**
CALIFORNIA ■ 949-498-2951 ■ 1-888-678-7224