


## Color Video Package



- Parts below are only included on UVPC
- Missing Parts, contact Pach and Company 1-888-678-7224
- Defective system under manufacturer warranty, call 1-888-678-7224 for advance replacement
- 24 Months warranty for complete system
- Manual is also available for download at www.pach-co.com



## <u>Installing the Camera in the AeGIS or Quantum system</u>

This camera package is designed to be mounted on the AeGIS and Quantum telephone entry systems and must be installed inside the system.

- Locate the camera mounting hole on AeGIS system telephone entry system, behind the front panel
- 2. Take the metal bar off
- 3. Install the camera, place adhesive tape (not included) on top of the camera
- 4. Replace the metal bar.

TECHNICAL SUPPORT IS AVAILABLE MON-FRI 7:30AM-3:30PM PST AT 1-888-678-7224

## OUT (not included) CUT2 CUT3 CUT4 CUT5 CCC Video Distribution **Amplifier** Video IN UVPB Color camera max. distance= 1300 feet B/W camera max. Distance= 1950 feet 2Vdc Power Supply Cat-5 UVPB (Video Balun) Connection (included) RCA (male)-BNC Adapter (not supply)

## TECHNICAL SPECIFICATION

*Image Sensor*: 1/3" Color CMOS Image Sensor.

<u>Pixels NTSC</u>: 510 (H) x 493 (V) <u>Lens</u>: 1/3" f=6 mm, F=1.8 mm

Resolution: more than 350TVL

Minimum Illustration: 3 Lux/ F1.2 (0 Lux with IR)

S/N Ratio: more than 72dB

Power Consumption: 12VDC/10mA (supplied)

Gamma Modification: 0.45

Auto Gain Control: more than 18dB

White Balance: Auto

Electronic Shutter: 1/60-1/5000 Sec

*Video Output*: 1.0 Vp-p Composite Vide0 Signal 75 Ohm

Operating Temperature: 14 °F to 140 °F

Dimension (HWD): 1" x 1" x 0.75" (include the lens).

*Mounting*: Must be installed inside our system.

Shipping Weight: 1 lb.